

Forestry loader new generation NORDIC



Optional

Base with feet - Non-proportional radio control

Electric Joystick - Independent installation

Proportional radio control - Un-proportional radio control

Forestral trailer models	Internal flatbed size
FN 60 - 6000 kg	1.80 x 3.60 m closed 1.80 x 5.00 Max extension
FN 80 - 8000 kg	2.00 x 4.50 m closed 2.00 x 6.00 m Max extension
FN 100 - 10000 kg DOUBLE AXLE	2.10 x 5.00 m closed 2.10 x 6.50 Max extension

TECHNICAL DATA

MODEL	TF 450 C NORDIC	TF 550 C NORDIC	TF 650 C NORDIC	TF 750 C NORDIC
	TF 450 C NORDIC PROFESSIONAL	TF 550 C NORDIC PROFESSIONAL	TF 650 C NORDIC PROFESSIONAL	TF 750 C NORDIC PROFESSIONAL
Arm length - to grab center (mm)	4698	5698	6900	8300
Weight Nordic (Kg)	700	800	950	1150
Weight Nordic Professional (Kg)	770	880	1045	1265
Max weight / Max Load	550	550	550	550
MAX height (mm)	6500	7500	8500	9500
Minimum required tractor	90 HP	110 HP	130 HP	150 HP
Central rotation	360°	360°	360°	360°
Unlimited grab rotation	360° rotatore T3	360° rotatore T3	360° rotatore T4	360° rotatore T5
Arms	2	2	2	2
Sliding hydraulic arms	1	1	1	2
Sliding hydraulic arm length (mm)	795	1145	1495	1890 + 1000
Grab Type	THLS 30	TP 120	TP 135	TP 150

