

Forestry trailer homologated and equipped for loader and drive 6000 kg



This trailer offers everything necessary for forestry work, according to your needs: the crane (TFC4200 VERSUS model) is equipped with a hydraulic rotating grab that allows transportation of logs while the trailer allows for the transportation of timber even on relatively steep slopes. Moreover, the trailer is also suitable for transporting cereals as well as many other uses.



This trailer can be homologated for 5000 kg while maintaining the same specifications.

TECHNICAL DATA

	FT60V
Body dimension (m)	1,80 x 3,50
Sides height (cm)	60
Trailer weight (kg)	1650
Tailgate opening	standard
Can be tipped in 3 directions	standard
Holes for posts	N. 8 2 front, 2 rear and 4 lateral
Hydraulic brake with 2 homologated pistons	standard
Tyres	111.5/80-15.3 18 PR Forestal use
Rear capstans	2
Capstan per side	1
Handwheel locking brake	standard
Feet with small wheel	standard
Drive axle with forestal tyres for traction	standard

Optional

Drop-down sides

Side protection cm 60

Zinc-plated sides for each set of 4 sides

Hydraulic feet

Reduction gear complete with cardan joints

Bevelled double sheet metal base with anti-slip corner pieces for logs

Bolsters

Note: This trailer can be homologated only with the product listed below
- Mod. TFC4200 VERSUS



Both COMPASS and VERTICAL feet are available

TECHNICAL DATA - TFC4200 VERSUS

	TFC4200 VERSUS
Arm length - to grab center (mm)	4200
Weight (Kg)	640
Max weight / Max Load (kg)	400
Max Height (mm)	5500
Minimum tractor power	55-60 HP
Central rotation	360°
Unlimited grab rotation	360° rotatore T1
Arms	2
Sliding hydraulic arms	1
Sliding hydraulic arm length (mm)	1000
Grab Type	THLS 30

Optional

- Excavation Kit
- Independent hydraulic system
- Supplemental G3 step-up gear unit with power drive through shaft
- Central seat (standard)
- Joystick
- Hydraulic arm (standard)
- Tow kit not approved for the road
- Double pump to connect to joystick
- 3-point connector for tractor
- Double stabilizer feet

