

## Self-loading salt spreader with scatter type spreading



Self-loading broadcast salt-spreader - The top of the line of Self-loading salt spreaders. A rotating plate optimises the distribution and regulates the span of the material being spread. The commands, positioned in the operator cabin, allow the distribution of the substance to be started and stopped. The machine comes equipped with a hydraulic cylinder that regulates the aperture and closure of the outlet.



## MODELS

	LENGHT	TYPE
SP 160 B	1,66 m	BASIC
SP 200 B	2,06 m	BASIC
SP 230 B	2,36 m	BASIC
SP 250 B	2,55 m	BASIC

B- BASE	SP 160 B	SP 200 B	SP 230 B	SP 250 B
Max size (m)	1,66	2,06	2,36	2,55
Spreading width (m)	min.2 mt- max 15 mt	min.2 mt- max 15 mt	min.2 mt- max 15 mt	min.2 mt- max 15 mt



BASE MODEL

Transmission unit external to the vat



INDUSTRIAL MODEL

Transmission unit inside the vat

### **WEIGHTS AND LOAD CAPACITIES**

<b>B - BASE</b>	<b>SP 160 B</b>	<b>SP 200 B</b>	<b>SP 230 B</b>	<b>SP 250 B</b>
<b>Min. - max weight (kg)</b>	350 - 370	370 - 395	490 - 510	530 - 550
<b>Min. - max capacity (lt)</b>	630 - 650	800 - 820	930 - 950	1100 - 1300

The fork attachment is provided only on models SP 250 B

### **ACCESSORIES**

Salt frangmeter roll

TECNOPLUS security system

Rear footprint lights

Covering cloth







Salt frangmeter rolle