

## Vibroflex harrows, fixed and foldable in two pieces



This harrow is equipped with square springs with teeth that are not fixed but rather elastic to offer a function between that of a extirpator and a traditional fixed-tooth harrow.

This harrow is available with either a fixed frame or in a folding frame for road transport.



**WITH FOUR HYDRAULIC CYLINDERS STANDARD  
AND CAGE ROLLER Ø 400 mm WITH SQUARE SPRINGS Ø 25X25 mm**

### **MODELES**

MODEL	WIDTH	FRAME	WEIGHT	N. SPRINGS
ERV300-IQ	3000 mm	FIXED	850 kg	16
ERV400-IQ	4000 mm	FOLDING	1.500 kg	22
ERV500-IQ	5000 mm	FOLDING	1.900 kg	28
ERV600-IQ	6000 mm	FOLDING	2.500 kg	34

Standard: 1 cage roller

Available Rollers

### **ACCESSORIES**

Rear footprint lights

Security panels

Lamellar roller + tubes Ø 400 mm

Parker roller, Ø 523 mm from point to point

Front levelling bar 3.00 m

Front levelling bar 4.00 m

Front levelling bar 5.00 m

Front levelling bar 6.00 m

**Double laminated rollers + tubes for 3.00 m**

**Double laminated rollers + tubes for 4.00 m**

**Double laminated rollers + tubes for 5.00 m**

**Double laminated rollers + tubes for 6.00 m**

**Spring mm 30x30**

**Ploughshare made of NiCrMo4**

## ***ATTACHMENT***



fixed and slitted pin for 4 - 5 - 6 mt

Fork attachment with



Bar attachment for 2.5 -

3 mt



Detail of squared spring

25x25 / 30x30



adjustment feature

Detail of depth