

Forestry loader new generation NORDIC



Optional

- Base with feet - Non-proportional radio control
- Electric Joystick - Independent installation
- Proportional radio control - Un-proportional radio control

Forestral trailer models	Internal flatbed size
FN 60 - 6000 kg	1.80 x 3.60 m closed 1.80 x 5.00 Max extension
FN 80 - 8000 kg	2.00 x 4.50 m closed 2.00 x 6.00 m Max extension
FN 100 - 10000 kg DOUBLE AXLE	2.10 x 5.00 m closed 2.10 x 6.50 Max extension

TECHNICAL DATA

MODEL	TF 450 C NORDIC	TF 550 C NORDIC	TF 650 C NORDIC	TF 750 C NORDIC
	TF 450 C NORDIC PROFESSIONAL	TF 550 C NORDIC PROFESSIONAL	TF 650 C NORDIC PROFESSIONAL	TF 750 C NORDIC PROFESSIONAL
Arm length - to grab center (mm)	4698	5698	6895	8295
Weight Nordic (Kg)	700	800	950	1150
Weight Nordic Professional (Kg)	770	880	1045	1265
Max weight / Max Load (kg) (senza pinza e rotore a 210 bar)	550	550	550	550
MAX height (mm)	6500	7500	8500	9500
Minimum required tractor	90 HP	110 HP	130 HP	150 HP
Central rotation	360°	360°	360°	360°
Unlimited grab rotation	360°	360°	360°	360°
Arms	rotatore T3 2	rotatore T3 2	rotatore T4 2	rotatore T5 2
Sliding hydraulic arms	1	1	1	2
Lunghezza 1° sfilo (mm)	795	1145	1495	1890
Portata 1° sfilo (kg)	550	550	550	650
Lunghezza 2° sfilo (mm)	-	-	-	1000
Portata 2° sfilo (kg)	-	-	-	550
Tipo Pinza	THLS 30	TP 120	TP 135	TP 150
Lunghezza 1° braccio (mm)	2200	2500	3000	3000
Portata 1° braccio (kg)	800	855	940	1079
Lunghezza 2° braccio (mm)	1700	2050	3000	3000
Portata 2° braccio (kg)	630	650	700	839