

Hydraulic grapple for excavators Mod. Professional LARGE CAPACITY



For excavators of up to 25 tons, for forestry and industrial uses

Made from Domex 710 steel and equipped with lock valve

Wood grabs are used to move, load and unload tree trunks cleaned from branches and ready to be transported and can be mounted on **forest cranes** of any size and range.

The Professional wood grab is used in forestry and industrial applications, for excavators up to 25 t. An important innovation is the splitting grapple that can be installed on a crane, which can split logs up to a diameter of 80 cm for the purpose of complementary work.

You get all the models **LARGE CAPACITY** by reducing the maximum width of opening with a more rounded shape that increases the performance of use and significantly the loading volume.

For example , a grapple of 1.35 m the opening will be of 1.20m.


For pressures greater than 250 bar a limit valve is installed (optional)

ESCAVATOR MATCHED



MODEL Professional	ESCAVATOR MATCHED
THL30 E	MAX 1,5 ton.
THL 30 Professional	MAX 2 ton.
THLS 30 Professional	MAX 4 ton.
TP 120 Professional	MAX 7 ton.
TP 135 Professional	MAX 12 ton.
TP 155 Professional	MAX 15 ton.
TP 175 Professional	MAX 20 ton.
TP 200 PRO	MAX 25 ton.

TECHNICAL DATA



MODEL	Weight kg	Lift Kg	MAX BAR	A mm	B mm	C mm	D mm	E mm	F mm	G mm	SP D mm	AREA mq	SP C mm
THL30 E	58	1000	210	1000	730	405	450	460	65	310	8	0,146	8
THL 30 Professional	71	1200	250	1000	730	405	450	460	65	310	10	0,146	10
THLS 30 Professional	89	1400	250	1000	730	405	450	460	65	310	10	0,146	20
TP 120 Professional	110	1700	250	1200	770	450	480	510	80	355	10	0,201	20
TP 135 Professional	155	2100	250	1350	880	500	540	550	90	370	12	0,255	20
TP 155 Professional	240	2700	250	1550	960	620	630	600	100	430	12	0,336	20
TP 175 Professional	340	3200	250	1750	1100	680	710	670	130	490	15	0,428	20
TP 200 Professional	540	3600	250	2000	1300	800	820	780	150	560	20	0,531	20

Grazie alla struttura centrale molto stretta ed ad uno spessore dell'acciaio molto elevato dove viene fissata la boccola del rotore è possibile garantire un' ottima tenuta anche con i rotatori a perno, permettendo così di risparmiare sul costo complessivo.

OPTIONAL

[*Accessori per pinze per tronchi, pinze da roccia, benna mordente, pinze con motosega, pinze selezionatrice, polipi per legna/rottami](#)

[*Accessori ROTATORI per pinze tronchi, pinze da roccia, benna mordente, pinze con motosega, pinze selezionatrice, polipi per legna/rottami](#)

Rotori per uso orizzontale/verticale per pinze mod. RF

	Rotori ad uso pendolare per pinze
	Forcella (su misura per mod. RF)
	Forcella (su misura per pinze)
	Valvola di MASSIMA per pressioni superiori ai 250 BAR
	Kit Benne per pinze modello comby
	Attacco rapido (specificare modello)

Download

 [Scarica il CERTIFICATO DI ORIGINE PINZE DA LEGNA \(77.5 KiB\)](#)