Hydraulic mulcher for excavators
Type SUPER FAST D

Working speed 4000 RPM



with direct trasmission

Le macchine sono corredate di nulla osta, abbinamento macchina e marchiature CE

HYDRAULIC SAFETY BLOCK

The machine is supplied as standard with the new Tecnomeccanica **“HYDRAULIC SAFETY BLOCK”** valve kit, an aluminum safety valve containing the following valves inside:

Tecnomeccanica S.r.l.
Via I° Maggio, 56 - 10035 Casale di Mazzè (TO)
Tel. +39 011 9830776 - Fax +39 011 9830776
www.tecnomecannicaformia.it

- Valve maximum pressure work hydraulic motor
- No-return valve in case of reverse connection of hydraulic pipes
- Shockproof valve that allows the rotor to stop proportionally
- One-way valve for connecting the drainage pipe to the return circuit

The machine works only with two pipes: delivery pipe and return pipe

Standard equipment

- Rear stone guard
- Hydraulic Safety Block
- Wear-resistant pads
- Straight knives + 2 Y- Tools B
- Two hydraulic pipes / hoses without quick coupling

Accessories on demand

- Attachment plate on demande
- Quick coupler

Technical Data

Models	Total Length (mm)	Length (mm)	Height (mm)	Working width (mm)	Weight (Kg)	Hydraulic motor	Oil flow rate
ST 500 D/7	450	650	420	500	78	GR2	25/28
ST 500 D/8	450	650	420	500	78	GR2	29/34
ST 650 D/8	450	800	420	650	95	GR2	29/34
ST 800 D/11	450	950	420	800	110	GR2	42/46
ST 800 D/14	450	950	420	800	110	GR2	52/56
ST 900 D/14	450	1.050	420	900	125	GR2	52/56
ST 900 D/17	450	1.050	420	900	125	GR2	65/71
ST 1000 D/17	450	1.150	420	1.000	140	GR2	65/71


Recommended excavators

Tecnomeccanica S.r.l.
Via I° Maggio, 56 - 10035 Casale di Mazzè (TO)
Tel. +39 011 9830776 - Fax +39 011 9830776
www.tecnomecannicaformia.it



Model	Recommended excavator
ST 500 D	1,6 - 2,5 t
ST 650 D	2,5 - 3,5 t
ST 800 D	3,5 - 5,0 t
ST 900 D	4,0 - 5,0 t
ST 1000 D	5,0 - 6,0 t

Tools

Tools	Description	Use	Model				
			ST 500 D	**ST 650 D**	**ST 800 D**	**ST 900 D**	**ST 1000 D**
	Straight + 2 Y knife	The tool is ideal for breaking up grass, small pieces of wood and branches up to 5-6 cm in diameter	16 Y + 8	24 Y + 12	32 Y + 16	36 Y + 18	38 Y +19

Video



[Trinciatutto - Testata trinciante per escavatori Mod. SUPER FAST D - ST 500D]

Tecnomeccanica S.r.l.
Via I° Maggio, 56 - 10035 Casale di Mazzè (TO)
Tel. +39 011 9830776 - Fax +39 011 9830776
www.tecnomecannicaformia.it

Tecnomeccanica S.r.l.
Via I° Maggio, 56 - 10035 Casale di Mazzè (TO)
Tel. +39 011 9830776 - Fax +39 011 9830776
www.tecnomecannicaformia.it