

Salt spreader for operating machines with scatter type spreading

Stainless steel disc as standard





PROFESSIONAL Model: max capacity from 0,60 to 1,15 m³

Models	Max size (m)	Min. weight (kg)	max capacity (m ³)	Spread (m)
SP 120 PT-S - 0,60	1,25	258	0,60	min.2 mt- max 12 mt
SP 140 PT-S - 0,67	1,46	304	0,67	min.2 mt- max 12 mt
SP 160 PT-S - 0,75	1,66	395	0,75	min.2 mt- max 12 mt
SP 200 PT-S - 0,92	2,06	485	0,92	min.2 mt- max 12 mt
SP 230 PT-S - 1,05	2,36	590	1,05	min.2 mt- max 12 mt
SP 250 PT-S - 1,15	2,55	630	1,15	min.2 mt- max 12 mt

PROFESSIONAL MAXI Model: max capacity from 1,19 to 1,93 m³

Models	Max size (m)	Min. weight (kg)	max capacity (m ³)	Spread (m)
SP 160 PT-S MAXI - 1,19	1,66	459	1,19	min.2 mt- max 12 mt
SP 200 PT-S MAXI - 1,48	2,06	550	1,48	min.2 mt- max 12 mt
SP 230 PT-S MAXI - 1,70	2,36	690	1,70	min.2 mt- max 12 mt
SP 250 PT-S MAXI - 1,93	2,55	780	1,93	min.2 mt- max 12 mt

Accessories

- Salt frangmeter roll
- Stainless steel tank
- Skid loader attachment
- Elettrovalvola 5 vie 12 volt per apertura e chiusura sportello da interno cabina
(IMPIANTO ELETTRICO MACCHINA OPERATRICE A CARICO DEL CLIENTE)

for PROFESSIONAL Models only

- Manual covering cloth